DEVELOPMENT AND DEMONSTRATION OF A BI-MODE FUEL CELL TRAIN

EU Project FCH2RAIL ERFA H2 Trains, Innsbruck, 25.06.2024 Holger Dittus



Fuel Cell Hybrid PowerPack for Rail Applications




DLR Hydrogen Research





Szenarienentwicklung, Technologiebewertung, marktwirtschaftliche und gesamtsystemische Analysen





Institute of Vehicle Concepts



Diesel traction vehicles in regional passenger transport Almost 2,900 diesel multiple units (DMU) in Germany




Diesel vehicles in regional rail transport

- 2,862 diesel multiple units
- >100 diesel locomotives
- Average age of diesel fleet: 16.5 a
- Registration peak around year 2000






https://www.now-gmbh.de/de/aktuelles/presse/hohes-marktpotenzial-alternativer-antriebe-im schienenverkehr



Diesel shunting locomotives 2800 shunters operated in Germany

Shunter inventory



- Currently approx. 2,800 shunting locomotives in Germany
- Mainly diesel locomotives in the fleet
- Frequently hydrodynamic drives
- Average fleet age 42 years








Project Overview





- Project dates: 1 January 2021 31 December 2024
- Total budget: 13,4 M€, max. contribution: 10 M€
- Stage of implementation 25.06.2024: 90%



This project has received funding from the Fuel Cells and Hydrogen 2 Joint Undertaking (now Clean Hydrogen Partnership) under Grant Agreement No 101006633. This Joint Undertaking receives support from the European Union's Horizon 2020 Research and Innovation program, Hydrogen Europe and Hydrogen Europe Research.

Main Objectives:


- 1. Develop, build, test and homologate a multipurpose Fuel Cell Hybrid PowerPack
- 2. Demonstrate FCHPP in a Bi-mode Civia multiple unit
- 3. Propose a normative framework for hydrogen in railway vehicles
- 4. Demonstrate competitiveness of fuel cell traction against existing diesel solutions
- 5. Identify and benchmark innovative solutions to improve energy efficiency





Focus of the project:

- Develop, build, test and homologate a multi-purpose Fuel Cell Hybrid PowerPack 1.
- 2. Demonstrate FCHPP in a Bi-mode Civia multiple unit











Fuel Cell Hybrid PowerPack for Rail Applications



WP8 Dissemination, Communication, Exploitation


Developing the Fuel Cell Hybrid PowerPack Definition of the requirements





Use cases have been analysed in Spain, Portugal, Germany and Slovakia

- DMUs
- Mainline locomotives
- Shunting locomotives




Many services have been analysed

- Spain and Portugal: 10 of 73 services
- Germany: 13 of 1417 services

Very different characteristics:

	min	max
Non <u>electrified section</u> (Km)	80	730
<u>Altitude</u> (m)	20	1000
Av. Distance btw. Stations (Km)	2	25




Global requirements defined:

- Power & energy
- Autonomy or range

Developing the Fuel Cell Hybrid PowerPack Definition of the requirements: Service Profiles acc. to EN50591





WP1: H2-Refuelling and H2-Storage Concepts



Challenges in Rail Applications:

- Storage concept 35 / 70 MPa or LH2
- Fast train refuelling, mobile / stationary
- Renewable H2 supply and logistics

Work in progress:

- Monitoring train refuelling processes
- Improving refueling times





Fig. 7 – Hydrogen refueling concepts for CGH₂ rail vehicle storage: variant a) - d), source own illustration.

Developing the Fuel Cell Hybrid PowerPack Definition of the components and architecture






FCHPP Architecture

- Scalable and modular
- Applicable for different rail applications (Multiple Unit, Mainline and Shunting Loco)

Components in FCH2RAIL

- Fuel Cells (TOYOTA)
- Energy storage system OESS (CAF)
- DC/DC converter (CAF)
- Energy management DASEM (CAF)
- Cooling system (Third Party)
- H2 Storage system (Third Party)

Developing the Fuel Cell Hybrid PowerPack Energy management



Challenges in FCHPP development and operation:

- 1) Design and dimensioning of fuel cell and energy storage systems
- 2) Optimisation of power requirements and power distribution between fuel cells and energy storage systems

13

FCH₃RAIL


Fuel Cell Hybrid PowerPack for Rail Application


Developing the Fuel Cell Hybrid PowerPack Energy management: Hybridisation Tool



Language	MATLAB
Energy management	Heuristic hysteresis with power tracking
Modelling approach	Functional programming: Reverse component models with power flow and iterative steps for dimensioning
Goal, specific features	 Component dimensioning Energy consumption calculation

➔ The hybridisation tool supports the FCHPP design and dimensioning






Developing the Fuel Cell Hybrid PowerPack Smart Energy and Speed Optimizer Rail SEnSOR



Language	MATLAB + IPOPT Toolbox
Energy management	Numerical optimization
Modelling approach	Functional programming: Train in specified environment, including track description, timetable, train and component models.
Goal, specific features	 Optimized energy consumption Optimized speed profile Simultaneous optimisation of energy consumption and speed profile



→ SEnSOR combines the optimisation of the driving profile and power distribution in the FCHPP

16

Developing the Fuel Cell Hybrid PowerPack Detailed design, manufacturing and testing the subsystems

Components tested at origin and ready for installation







Development of Hardware in the Loop (HIL)





- HIL test bench developed in CAF
- HIL includes:
 - Electronic controllers of the subsystems of the Fuel Cell Hybrid PowerPack
 - New Train Control and Monitoring System (TCMS)
 - Traction control unit of the existing traction equipment in the CIVIA train
 - TCMS of the CIVIA train

 Functionality of the new FCHPP and interaction with existing train control and traction equipment is extensively tested

Testing the FCHPP – Start in February '22






Facilities at CNH2 (prototypes area):

- Clean and clear
- Nothing implemented

Testing the FCHPP Fuel cells and H2 supply








Fuel cells, cooling systems and hydrogen supply and monitoring panel

Testing the FCHPP Energy Storage and DC/DC







Energy storage with BTMS and DC/DC placing, mechanical and electrical installation

Testing the FCHPP: Summary



Test program:

- Standard polarization curves for fuel cells, etc.
- H2 consumption tests, driving cycle test, ramp-up test, etc.
- Tests related especially to the specific use cases / service profiles / railway profiles, etc.


Results:

- More than 220 kg of green H2 consumed during the tests.
- Detailed knowledge of the systems and subsystems performance was obtained.
- Control and energy management system was optimized.
- → Full functionality and requested performance of the FCHPP is achieved.



Train Demonstrator Development






A1/A2

A3

A1/A2

homologation



development

H2 supply and refuelling Portable H2 refuelling station in the FCH2RAIL project



Fill up once a day - what does it take?





1x compressor container, 2x high pressure storage containers

23



Container with dispenser, pressure control and control system for the HRS











Project Highlights

FCH2RAIL project: First hydrogen train on the Spanish railway network



The testing phase in the Spanish tracks has started with the first test run on the Zaragoza-Canfranc line, in the Aragonese Pyrenees and it will continue on lines in Madrid and Galicia.





Video: First hydrogen train on Spanish and Portuguese lines 12.06.2024 READ MORE *



Video: Hydrogen refuelling station in service

READ MORE



The hydrogen train finalises tests in Galicia

READ MORE #

.



The first Hydrogen train carried out tests on the Portuguese railway network 16.04.2024



The Demonstrator Train proves more than 800 km autonomy in the Madrid testing campaign 04.03.2024

READ MORE #

H. Dittus, FCH2RAIL, Innsbruck, 25.06.2024

Data of Demo-Train and Demonstration campaign Visit the Train – FCH2RAIL



Train Demonstrator:

- 3 car Civia Unit with 2 FCHPP
- Pantograph for 3kV DC catenary
- ESS:
 - Max Power: 1044 kW
 - Capacity: 238 kWh
- Fuel Cells:
 - Six Toyota 2nd generation Fuel Cell Modules
 - 80 kW each, 480 kW in total
- H2 Storage:
 - 160 kg @350 bar in total, type III
 - 4 racks, 8 vessels/rack, 5 kg/vessel



Demonstration campaign:

- Several lines in Spain and Portugal
- 10,000 km in H2 mode
- 6,000 km in electric mode
- >2,000 kg H2 consumed
- >800 km autonomy

Testing the FCHPP



https://youtu.be/mC7EGb9VA7w

Train transformation



https://youtu.be/bFBR6nhyEVI

The Journey Begins!



https://youtu.be/s4JfnDbrLW8

HRS Service



H2 Train Service Experience



https://youtu.be/fFuYwuVSyII